

7037 Old Madison Pike, Suite 410 Huntsville, AL 35806 Tel: (800) MILTOPE

www.mymiltope.com

RTHD-3

Windows® version

RUGGED Tactical Handheld Computer

A tactical computer in the palm of your hand

KEY FEATURES

- . 6" HD LCD
- . 850 nit sunlight readable display
- . NVIS compatibility option 0 20 nits
- . Intel® i processor
- . Microsoft® Windows® 10 IoT Enterprise
- 16GB RAM, 512GB Mass Storage
- · Walkie-talkie communication
- Fully Rugged Design
- Hot swappable battery pack



The Rugged RTHD-3 for Windows® lightweight handheld system delivers shared situational awareness data to the war fighter. The RTHD-3 brings powerful mobile performance, a 6.0" sunlight readable touchscreen, an Intel® 12th Generation Core i7 processor, and multi-mission functionality. In situations where failure comes at a high cost, Miltope's long history of rugged systems is there to ensure mission success.

SPECIFICATIONS

SYSTEM

CPU Intel® 12th Generation Core i7 processor Windows

Operating System Microsoft® Windows® 10 IoT Enterprise

RAM 16GB

Storage 512GB Primary Storage Capacity

SD Card Slot Sealed secured cover requiring special tool access

NIST Compliance NIST compliant BIOS

Display 6" High-Brightness (850 nits) touchscreen

Display Resolution 1440 x 720

Microphone 1 (Optional remove at production)

Speaker Built-in speaker (Optional remove at production) Wireless Features Wi-Fi, Bluetooth removed (Optional add at production)

Switch & Buttons 1 power button, 1 Day/Night Vision Switch; 2 Push-to-talk buttons;

2 brightness control buttons; 2 programmable touch buttons



USB Port 1 Type-C; 1 USB-A

Ethernet Ethernet 10/100/1000MB Base-T LAN

DC Power In **Power**

MECHANICAL AND ENVIRONMENTAL

AC/DC Adapter Input: 100 - 240V AC Output: 15V DC, 3A **Battery Pack** Hot swappable battery, 7.6V, 3100mAh

Enclosure ABS + PC plastic and magnesium-aluminum alloy

Dimensions (HxWxD) 3.7 x 7.6 x 1.3 in/ 95 x 193 x 32 mm

Weight 1 lb/454 g

Durability IP65 and MIL-STD-810G Regulatory CE, FCC Class B, RoHS, UL Humidity 0% - 90% non-condensing

Temperature Operation: 0°C~ 50°C (32°F ~ 122°F)

Storage: $-20^{\circ}\text{C} \sim 60^{\circ}\text{C} (-4^{\circ}\text{F} \sim 140^{\circ}\text{F})$

NETWORK INTERFACE

WLAN Wi-Fi 802.11ax, 2.54/5GHz Dual Band

BT Yes Long-Range BT Yes **GPS** No







ACCESSORIES

DIGTAL PEN

4-BAY SYSTEM CHARGER

TACTICAL VEST MOUNT



6-BAY BATTERY CHARGER

BATTERY PACK



